
Technisches Datenblatt

Technical data sheet

Starke Verbindung
Kluge Technik
Strong contacts
Clever technology





PROFI-DESIGN Abschlussprofil Nr. 324, 21 x 6 mm

- Aluminium.
- Für Belagstärken von 4 - 7,5 mm.
- Ideal für Wandanschlüsse und den Abschluss an Balkontüren.
- Inklusive Basisprofil.

TÜV Zertifikat-Nr. 44 780 14206207
DBGM 20 2012 102 304.0

Oberprofil (Aluminium)

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)

Basisprofil (Kunststoff)

Werkstoff:	Hart-PVC
Dichte:	1,44 g/cm³ (DIN EN 53 479)
Grenzbiegespannung:	71,6 N/mm² (DIN EN 53 452)
Kerbschlagzähigkeit:	18 mJ/mm² (DIN EN 53 452)
Brandverhalten:	B1 (schwer entflammbar)

Lieferumfang: Kunststoff-Basisprofil

Geeignet für:	Designbelag / LVT Click und Loose Lay
Montageart:	Clipsen
Längen:	270 cm, 100 cm, 90 cm
Farben:	sahara, silber, bronze, Edelstahl matt, Edelstahl poliert, Edelstahl gebürstet, schwarz eloxiert

Speziell für schwimmend verlegte Designbeläge wurde das Profi-Design Clipsprofilsystem entwickelt. Die verzahnten Profilstege des Oberprofils rasten sicher in den trapezförmigen Aufnahmen des Basisprofils ein. Dabei kann das Oberprofil leicht verkippen und sich variabel in Höhe und Neigung dem Bodenbelag anpassen.
Die schmalen, flachen Profile überzeugen durch eine besonders schöne Optik und bieten gleichzeitig großzügige Dehnungsfugen für die Dimensionsschwankungen des Bodenbelages. Bei Bedarf können die Oberprofile gelöst und anschließend wieder im Basisprofil verankert werden.
Profi-Design Profile sind in sieben modernen Eloxaltönen lieferbar, u. a. in Edelstahl-Optiken mit gebürsteter oder polierter Oberfläche.

PROFI-DESIGN edge section no. 324, 21 x 6 mm

- Aluminium.
- For covering thicknesses from 4 - 7.5 mm.
- Ideal for wall connections and the joints within balcony doors.
- Including base section.

TÜV certification no. 44 780 14206207
DBGM 20 2012 102 304.0

Upper section (Aluminium)

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)

Base section (Kunststoff)

Material:	rigid PVC
Density:	1,44 g/cm³ (DIN 53 479)
Flexural stress:	71,6 N/mm² (DIN 53 452)
Notched impact strength:	18 mJ/mm² (DIN 53 452)
Fire behaviour:	B1 (hardly inflammable)

Included: PVC base section

Suitable for:	Design flooring / LVT click and loose lay
Installation:	clipsing
Lengths:	270 cm, 100 cm, 90 cm
Colours:	sahara, silver, bronze, stainless steel matt, stainless steel polished, stainless steel brushed, black anodised

The new Prinz PROFI-DESIGN section system was specially developed for floating installation of design floorings, 4 mm thick and above. The curved-toothed tie-bars of the top section snap safely in the trapezoidal slots of the base section. This enables the top section to tilt easily and to adapt automatically to the height and inclination of the floor covering.
As required, the top sections can be removed and then re-anchored in the base section.
The discreet and shallow top sections skilfully draw attention to the floor design while providing ample room for the extension joints.

Carl Prinz GmbH & Co. KG
von-Monschaw-Str. 5, D-47574 Goch
www.carlprinz.de

Mit Erscheinen dieses Dokuments verlieren alle Vorgängerversionen ihre Gültigkeit.
With publication of this document all former versions are invalid.